

BUILDING SPECIFICIATIONS

LOCATION	Full Block on West Side of Eighth Avenue Between 49th and 50th Streets		VERTICAL TRANSPORTATION	Twenty two (22) destination dispatch passenger elevators, three (3) freight elevators and two (2) loading dock truck elevators Four (4) escalators Loading dock located on 50th Street	
YEAR BUILT	1989. Renovated in 2013				
ARCHITECT	Skidmore, Owings & Merrill, LLP - David Childs			C C	
			HVAC/SUPPLEMENTAL COOLING	DX package AC units located on each non-Nomura floor.	
BUILDING SIZE	2,051,943 rsf			• Floors 11-14	Two (2) 60-ton units
				• Floor 17	Two (2) 50-ton units
BUILDING HEIGHT Forty nine (49) floo		rs		• Floor 18	Two (2) 50-ton units
				• Floors 20-48	One (1) 60-ton units
BUILDING CONSTRUCTION	 Conventional stru 	ictural steel beams and columns with reinforced		• Floor 49	One (1) 45-ton units
	concrete floor slab	5		The heating system consists of high pressure utility	
	 The exterior walls 	are finished with brick masonry veneer surrounding		company steam se	rvice.
	aluminum framed '	'punched" windows. The lower floors are finished with			
	a granite veneer, a	nd the Building's base includes precast concrete on	ELECTRIC	Six (6) 4,000 amp services at 277/480 volts Eight (8) watts/SF available for tenant use	
	tower corners and	stone surrounding the large entrance openings			
FLOOR LAYOUT	Center core		LIFE/SAFETY	Addressable Class E system	
			,	Building is fully sprinklered	
FLOOR LOAD	50 lbs. psf			Danan ig io ian y opi	
	00 (30) po.		GENERATORS	Emergency genera	tor covering all life safety systems
FLOOR SIZES	Floor 2 36,000 rsf			400-425kW excess capacity available for tenant tie-in	
	Floor 4	72,400 rsf			for 1,000kW tenant generator
	Floors 5-6	54,800 rsf			, J
	Floors 7-14	47,500 rsf	SECURITY ACCESS	Coordinated prog	ram of controlled electronic access, electronic
	Floors 15-19	40,000 - 42,000 rsf			uniformed security guards on a 24/7 basis,
	Floors 20-47	32,500 - 34,500 rsf			les, messenger center and extensive CCTV coverage
	Floor 48	24,300 rsf			
	Floor 49	20,500 rsf	TELECOM/CABLE	AT&T, Century Lin	ık, Cogent, Crown Castle/Lightower,
			-	-	'erizon, Zayo Group
TYPICAL SLAB HEIGHTS	13'			Wired Certified Plati	
				DAS for enhanced of	cellular service
COLUMN SPACING	Column free tower floors (20-49)				
	Virtually column free base floors (2-19)		TRANSPORTATION Direct access to C & E subway lines		